

8" 2-Way Coaxial All Weather Loudspeaker HSK-108TS

Description:

The HSK-108TS 8" all-weather outdoor loudspeaker offers superior voice and music reproduction with a 180° x 90° coverage angle from a durable UV protected ABS construction. Outdoor level of IP66 rated for long-lasting reliability in harsh environmental conditions, this 100V/70V transformer built-in all weather outdoor loudspeaker incorporates a coaxial high-power 8" woofer and 3" tweeter that delivers full range frequency response up to 80-20KHz to meet all indoor and outdoor music applications. The all weather loudspeaker is perfect for background and foreground music, paging, and public address & voice evacuation in sports hall, football field, playground, park and outdoor live performance applications.



Feature:

- . Commercial full weatherproof horn speaker with 100V/70V transformer
- . Application of outdoor sound applications of sports hall, football field, playground, park
- . Superior sound quality of very clear voice restoration
- . Two way 8" woofer with 3" tweeter
- . RMS 160 Watt 70V/100V transformer with 8Ω power tapping
- . Power tapplings of 160W-80W-40W & 8Ω bypass
- . Waterproof outdoor use level of IP66
- . Outdoor weather safe connection with a recessed terminal block and waterproof seal cover
- . Fiber-reinforced plastic enclosure with aluminum alloy grill in black
- . U-Shaped wall mounting stainless bracket is supplied
- . Multiple combination of outdoor line array loudspeakers

Specification:

Model	HSK-108TS
Description	8" 2-Way Coaxial All Weather Loudspeaker
Power Output	160W RMS and 300W Max.
Impedance	8 Ohms
Power Tapping	160W-80W-40W & 8Ω bypass
Frequency Response	80-20KHz
SPL (@1W/m)	98dB and Max 108dB
Speaker Unit	Waterproof 8"woofer + 3" tweeter
IP Rate	IP66
Dispersion Angle	Horizontal: 180°, Vertical: 90°
Operation Temp	-22°C to +55°C
Dimension	330x255x310mm
Material	Fiber-reinforced plastic enclosure with aluminum alloy grill in black, stainless bracket
Weight	9.5kg

Rear View:



8" 2-Way Coaxial All Weather Loudspeaker HSK-108TS



Frequency Response VS SPL Diagrams:

